

QA Range Mini Rail 13 mm Hydraulic-Magnetic



QA-1(13)



QA-2(13)



QA-3(13)



QA-N-4(13)

Circuit Breakers 3 kA Curve 3 (Standard) Mini Rail Mounting, 57 mm Escutcheon								L1
Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QA-1(13) (White Handle)	1	240 Vac	3	13 (1 Module)	12	1, 2, 5	R 171.00	QAL183...
						10, 15, 20	R 174.00	
						25, 30, 35, 40	R 195.00	
						45, 50, 60	R 201.00	
QA-2(13) (White Handle)	2	415 Vac	3	26 (2 Modules)	6	1, 2, 5	R 654.00	QAL283...
						10, 15, 20	R 671.00	
						25, 30, 35, 40	R 690.00	
						45, 50	R 742.00	
QA-3(13) (White Handle)	3	415 Vac	3	39 (3 Modules)	4	5	R 966.00	QAL383...
						10, 15, 20	R 1 050.00	
						25, 30, 35	R 1 065.00	
						40, 45, 50	R 1 086.00	
QA-N-2(13) (White/Green Handle)	1 + N	240 Vac	3	26 (2 Modules)	6	1, 2, 5, 10, 15, 20	R 462.00	QAL213...
						25, 30, 35, 40, 45, 50	R 489.00	
						60	R 499.00	
QA-N-4(13) (White/Green Handle)	3 + N	415 Vac	3	52 (4 Modules)	3	5, 10, 20, 25	R 1 255.00	QAL413...
						30, 35, 40, 45, 50	R 1 284.00	

Switch Disconnectors 3 kA, Mini Rail Mounting 57 mm Escutcheon								L1
Type	Poles	Voltage	Withstand kA ¹	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QA-S-1(13) (Green Handle)	1	240 Vac	3	13 (1 Module)	12	63	R 169.00	QAL10063
QA-S-2(13) (Green Handle)	2	415 Vac	3	26 (2 Modules)	6	63	R 339.00	QAL20063
QA-S-3(13) (Green Handle)	3	415 Vac	3	39 (3 Modules)	4	63	R 522.00	QAL30063
QA-S-4(13) (Green Handle)	4	415 Vac	3	52 (4 Modules)	3	63	R 657.00	QAL40063

Notes:

Max cable size 25 mm²

The above Voltages and kA ratings are in accordance with SANS specifications (see side of product)

The front printing on the product refers to Voltages and kA ratings in accordance with IEC specifications

1. Required to be backed up by a suitable Short Circuit Protection Device (SCPD)

Please contact CBI for Amp Ratings not listed



QAC Single Phase Changeover Switch Range Dual Mount and Dual Escutcheon



QAC-4(13)

NEW!!
Dual mount
Dual escutcheon

Changeover Switch 3 kA, Mini Rail and DIN Rail Mounting 57 mm and 45 mm Escutcheon								AB
Type	Modules	Voltage	Withstand kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QA single phase changeover switch	4	240 Vac	3	52 mm (4 modules)	1	63 A	R 501.00	QAC40063

Notes:

Max cable size 25 mm²

The front printing on the product refers to Voltages and kA ratings in accordance with IEC specifications
For single phase installations only

QIL Indicator Light Range Mini and DIN Mount



QIL-1(13)



QIL-2(13)



QIL-1(13)D



QIL-2(13)D

NEW!

Indicator Light, Mini Rail Mounting 57 mm Escutcheon							AB
Type	Modules	Voltage	Width (mm)	Std. Pack	Price Ea. excl. VAT	Order No.	
QIL-1(13) (Red indicator)	1	240 Vac	13 mm (1 module)	12	R 61.00	QILM0001	
QIL-1(13) (Green indicator)	1	240 Vac	13 mm (1 module)	12	R 61.00	QILM0101	
QIL-2(13) (Live 1 red indicator, Live 2 green indicator)	2	240 Vac	26 mm (2 module)	12	R 112.00	QILM0002	
Indicator Light, DIN Rail Mounting 45 mm Escutcheon							AB
QIL-1(13)D (Red indicator)	1	240 Vac	13 mm (1 module)	12	R 61.00	QILD0001	
QIL-1(13)D (Green indicator)	1	240 Vac	13 mm (1 module)	12	R 61.00	QILD0101	
QIL-2(13)D (Live 1 red indicator, Live 2 green indicator)	2	240 Vac	26 mm (2 module)	12	R 112.00	QILD0002	

QF Range Dual Mount 13 mm Hydraulic-Magnetic



QF-1(13) C1



QF-2(13) C1



QF-1(13)



QF-2(13)



QF-3(13)



QF-N-4(13)

Circuit Breakers 6 kA Curve 1 (Special) Mini and DIN Rail Mounting, 57 mm Escutcheon								L2
Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(13) (Orange Handle)	1	240 Vac	6	13 (1 Module)	12	5, 10, 15, 20, 25	R 264.00	QFA181...
QF-2(13) (Orange Handle)	2	415 Vac	6	26 (2 Modules)	6	15, 20	R 974.00	QFA281...
QF-3(13) (Orange Handle)	3	415 Vac	6	39 (3 Modules)	4	5, 10, 15, 20	R 1 461.00	QFA381...
						25	R 1 471.00	
QF-N-2(13) (Orange/Green Handle)	1 + N	240 Vac	6	26 (2 Modules)	6	5, 10, 15, 20	R 559.00	QFA211...
						25	R 565.00	

Circuit Breakers 6 kA Curve 2 (Standard) Mini and DIN Rail Mounting, 57 mm Escutcheon								L2
Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(13) (White Handle)	1	240 Vac	6	13 (1 Module)	12	1, 2	R 275.00	QFA182...
						5	R 188.00	
						10, 15, 20	R 192.00	
						25	R 214.00	
QF-2(13) (White Handle)	2	415 Vac	6	26 (2 Modules)	6	5	R 711.00	QFA282...
						10, 15, 20	R 731.00	
						25	R 796.00	
QF-3(13) (White Handle)	3	415 Vac	6	39 (3 Modules)	4	5	R 1 140.00	QFA382...
						10, 15, 20	R 1 140.00	
						25	R 1 159.00	
QF-N-2(13) (White/Green Handle)	1 + N	240 Vac	6	26 (2 Modules)	6	5, 10, 15, 20	R 502.00	QFA212...
						25	R 534.00	
QF-N-4(13) (White/Green Handle)	3 + N	415 Vac	6	52 (4 Modules)	3	5, 10, 15, 20, 25	R 1 366.00	QFA412...

Notes:

Max cable Size 25 mm²

The above Voltages and kA ratings are in accordance with SANS specifications (see side of product).

The front printing on the product refers to Voltages and kA ratings in accordance with IEC specifications.

1. Required to be backed up by a suitable Short Circuit Protection Device (SCPD)

Please contact CBI for Amp ratings not listed



QF Range Dual Mount 13 mm Hydraulic-Magnetic

Switch Disconnectors 6 kA, Mini and DIN Rail Mounting, 57 mm Escutcheon								L2
Type	Poles	Voltage	Withstand kA ¹	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-S-1(13) (Green Handle)	1	240 Vac	6	13 (1 Module)	12	63	R 196.00	QFA10063
QF-S-2(13) (Green Handle)	2	415 Vac	6	26 (2 Modules)	6	63	R 369.00	QFA20063
QF-S-3(13) (Green Handle)	3	415 Vac	6	39 (3 Modules)	4	63	R 576.00	QFA30063
QF-S-4(13) (Green Handle)	4	415 Vac	6	52 (4 Modules)	3	63	R 739.00	QFA40063

Notes:

Max cable size 25 mm² - QF(13)

The above Voltages and kA ratings are in accordance with SANS specifications (see side of product).

The front printing on the product refers to Voltages and kA ratings in accordance with IEC specifications.

1. Required to be backed up by a suitable Short Circuit Protection Device (SCPD).



QF Range Dual Mount Low Rating 26 mm Hydraulic-Magnetic



QF-1(26)



QF-2(26)



QF-N-4(26)

Circuit Breakers 6 kA Curve 1 (Special) Mini and DIN Rail Mounting, 57 mm Escutcheon								L2
Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(26) (Orange Handle)	1	240 Vac	6	26 (1 Module)	12	5, 10, 15, 20	R 268.00	QFE181...
						25, 30, 35, 40, 45, 50, 63	R 275.00	
QF-2(26) (Orange Handle)	2	415 Vac	6	52 (2 Modules)	6	10, 20	R 982.00	QFE281...
						25, 30, 40, 50, 63	R 986.00	
QF-3(26) (Orange Handle)	3	415 Vac	6	78 (3 Modules)	4	5	R 1 469.00	QFE381...
						10, 15, 20	R 1 472.00	
						25, 30, 35, 40, 45, 50, 63	R 1 475.00	

Circuit Breakers 6 kA Curve 2 (Standard) Mini and DIN Rail Mounting, 57 mm Escutcheon								L2
Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(26) (White Handle)	1	240 Vac	6	26 (1 Module)	12	1, 2	R 290.00	QFE182...
						5, 10	R 182.00	
						15, 20, 25, 30	R 195.00	
						35, 40, 45, 50, 63	R 206.00	
QF-2(26) (White Handle)	2	415 Vac	6	52 (2 Modules)	6	5	R 719.00	QFE282...
						10, 15, 20	R 731.00	
						25, 30, 35, 40	R 806.00	
QF-3(26) (White Handle)	3	415 Vac	6	78 (3 Modules)	4	45, 50, 63	R 817.00	QFE382...
						5, 10, 15, 20	R 1 050.00	
QF-N-2(26) (White/ Green Handle)	1 + N	240 Vac	6	52 (2 Modules)	6	25, 30, 35, 40, 45, 50, 63	R 1 059.00	QFE212...
						5, 10, 15, 20	R 484.00	
QF-N-4(26) (White/ Green Handle)	3 + N	415 Vac	6	104 (4 Modules)	3	25, 30, 35, 40	R 505.00	QFE412...
						45, 50, 63	R 564.00	
						5	R 1 154.00	
						10, 20	R 1 368.00	
						25, 30, 35	R 1 449.00	
						40	R 1 469.00	
						45, 50, 63	R 1 589.00	

Notes:

1. Required to be backed up by a suitable Short Circuit Protection Device (SCPD).
Max cable size up to 50 mm²



QF Range Dual Mount High Rating 26 mm Hydraulic-Magnetic



Circuit Breakers 6 kA Curve 1 (Special) Mini and DIN Rail Mounting, 57 mm Escutcheon L2

Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(26) (Orange Handle)	1	240 Vac	6	26 (1 Module)	12	70, 80	R 443.00	QFE181...
						90, 100, 125	R 635.00	
QF-2(26) (Orange Handle)	2	415 Vac	6	52 (2 Modules)	6	70, 80	R 1 434.00	QFE281...
						90, 100, 125	R 1 561.00	
QF-3(26) (Orange Handle)	3	415 Vac	6	78 (3 Modules)	4	70, 80	R 2 155.00	QFE381...
						90, 100, 125	R 2 447.00	

Circuit Breakers Curve 1 (Special) 6 kA, Dual Mounting, 57 mm Escutcheon L2

Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-N-2 (26)-DM (Orange/Green Handle)*	2	240 Vac	6	26 (2 Modules)	12	63	R 679.00	QFE21163
						100	R 756.00	QFE211100
						125	R 756.00	QFE211125

Circuit Breakers 6 kA Curve 2 (Standard) Mini and DIN Rail Mounting, 57 mm Escutcheon L2

Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(26) (White Handle)	1	240 Vac	6	26 (1 Module)	12	70, 80	R 388.00	QFE182...
						90, 100, 125	R 450.00	
QF-2(26) (White Handle)	2	415 Vac	6	52 (2 Modules)	6	70, 80	R 1 350.00	QFE282...
						90, 100, 125	R 1 470.00	
QF-3(26) (White Handle)	3	415 Vac	6	78 (3 Modules)	4	70, 80	R 1 942.00	QFE382...
						90, 100, 125	R 2 330.00	
QF-N-2(26) (White/Green Handle)	1 + N	240 Vac	6	52 (2 Modules)	6	70, 80	R 844.00	QFE212...
						90, 100, 125	R 853.00	
QF-N-4(26) (White/Green Handle)	3 + N	415 Vac	6	104 (4 Modules)	6	70, 80	R 2 740.00	QFE412...
						90, 100, 125		

Switch Disconnectors 6 kA, Mini and DIN Rail Mounting, 57 mm Escutcheon L2

Type	Poles	Voltage	Withstand kA ¹	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-S-1(26) (Green Handle)	1	240 Vac	6	26 (1 Module)	12	63	R 218.00	QFE10063
						100, 125	R 369.00	QFE100...
QF-S-2(26) (Green Handle)	2	415 Vac	6	52 (2 Modules)	6	63	R 431.00	QFE20063
						100, 125	R 708.00	QFE200...
QF-S-3(26) (Green Handle)	3	415 Vac	6	78 (3 Modules)	4	63	R 670.00	QFE30063
						100, 125	R 1 170.00	QFE300...
QF-S-4(26) (Green Handle)	4	415 Vac	6	104 (4 Modules)	3	63	R 838.00	QFE40063
						100, 125	R 1 560.00	QFE400...

Notes:

Max cable size up to 50 mm²

1. Required to be backed up by a suitable Short Circuit Protection Device (SCPD).



QF Range DIN Rail 18 mm Hydraulic-Magnetic



QF-1(18)

QF-2(18)

QF-3(18)

QF-N-4(18)

Circuit Breakers 6 kA Curve 1 (Special) DIN Rail Mounting, 45 mm Escutcheon								L2
Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(18)-D (Orange Handle)	1	240 Vac	6	18 (1 Module)	12	6, 10, 16, 20	R 266.00	QFD181...
						25, 32, 40, 50, 63	R 274.00	
QF-2(18)-D (Orange Handle)	2	415 Vac	6	36 (2 Modules)	6	6, 10, 16, 20	R 982.00	QFD281...
						25, 32, 40, 50, 63	R 985.00	
QF-3(18)-D (Orange Handle)	3	415 Vac	6	54 (3 Modules)	4	6, 10, 16, 20	R 1 471.00	QFD381...
						25, 32, 40, 50, 63	R 1 475.00	

Circuit Breakers 6 kA Curve 2 (Standard) DIN Rail Mounting, 45 mm Escutcheon								L2
Type	Poles	Voltage	kA	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-1(18)-D (White Handle)	1	240 Vac	6	18 (1 Module)	12	1, 2	R 290.00	QFD182...
						6, 10, 16, 20	R 184.00	
						25, 32	R 207.00	
						35, 40, 50, 63	R 212.00	
QF-2(18)-D (White Handle)	2	415 Vac	6	36 (2 Modules)	6	6	R 719.00	QFD282...
						10, 16, 20	R 731.00	
						25, 32, 40	R 807.00	
QF-3(18)-D (White Handle)	3	415 Vac	6	54 (3 Modules)	4	6	R 1 057.00	QFD382...
						10, 16, 20	R 1 050.00	
						25, 32, 40, 45, 50, 63	R 1 059.00	
QF-N-2(18)-D (White / Green Handle)	1 + N	240 Vac	6	36 (2 Modules)	6	6, 10, 16, 20	R 489.00	QFD212...
						25, 32, 40	R 508.00	
						45, 50, 63	R 568.00	
QF-N-4(18)-D (White / Green Handle)	3 + N	415 Vac	6	72 (4 Modules)	3	10, 20	R 1 367.00	QFD412...
						25, 32, 40	R 1 447.00	
						50, 63	R 1 466.00	

Switch Disconnectors 6 kA, DIN Rail Mounting, 45 mm Escutcheon								L2
Type	Poles	Voltage	Withstand kA ¹	MCB Width (mm)	Std. Pack	Ratings (A)	Price Ea. excl. VAT	Order No.
QF-S-1(18) (Green Handle)	1	240 Vac	6	18 (1 Module)	12	63	R 218.00	QFD10063SI
QF-S-2(18) (Green Handle)	2	415 Vac	6	36 (2 Modules)	6	63	R 431.00	QFD20063SI
QF-S-3(18) (Green Handle)	3	415 Vac	6	54 (3 Modules)	4	63	R 669.00	QFD30063SI
QF-S-4(18) (Green Handle)	4	415 Vac	6	72 (4 Modules)	3	63	R 814.00	QFD40063SI

Notes:

Max cable size up to 35 mm²

The above Voltages and kA ratings are in accordance with SANS specification (see side of product).

The front printing on the product refers to Voltages and kA ratings in accordance with IEC specifications.

Use curve 1 for motor protection.



QF Range DIN Rail Hydraulic-Magnetic Earth Leakages (30 mA)



QF14AD



QF14CD

DIN Rail Mount									
Type	Poles	Voltage	kA	mA	Width (mm)	Std. Pack	Rating (A)	Price Ea. excl. VAT	Order No.
DIN Commercial / Industrial Earth Leakage Protection Device Single Phase with Overload Protection (DIN Mount)									L2
QF14AD	1 + N	240 Vac	6	30	36	10	6, 10, 16, 20, 32, 40, 50, 63	R 2 135.00	QF14AD2...
DIN Commercial / Industrial Earth Leakage Protection Device Single Phase without Overload Protection (DIN Mount)									L2
QF14CD'	1 + N	240 Vac	6	30	36	10	63	R 1 474.00	QF14CD63



QA, QF & SF Range Earth Leakages - Hydraulic-Magnetic



1. Special Earth Leakage Protection Devices

All products manufactured by CBI to meet special non-standard requirements of customers will be quoted for (Price On Request).

2. Standard Current Ratings

Ampere ratings indicated are standard. Non-standard ratings can be provided (POR).

3. Earth Leakage Protection Devices Sensitivities

Sensitivities indicated are standard. Non-standard sensitivities can be provided (POR).

Earth Leakage Protection Devices Abbreviation Codes

Suffix A

Earth Leakage protection device with overload, Single pole and Neutral / 3 pole and Neutral versions.

Suffix C

Earth Leakage protection device (switch disconnecter, non overload), single pole and 3 pole versions.

Dual and Mini Rail Mount									
Type	Poles	Voltage	kA	mA	Width (mm)	Std. Pack	Rating (A)	Price Ea. excl. VAT	Order No.
Residential / Commercial Earth Leakage Protection Device Single Phase with Overload Protection (Dual Mount)									
QA17A	1 + N	240 Vac	3	30	26	10	5, 10, 15, 20, 25, 30, 40, 50, 63	R 1 978.00	QA17A...
Residential / Commercial Earth Leakage Protection Device Single Phase without Overload Protection (Dual Mount)									
QA17C ¹	1 + N	240 Vac	3	30	26	10	63	R 1 028.00	QA17C63
Commercial / Industrial Earth Leakage Protection Device Single Phase with Overload Protection (Dual Mount)									
QF17A	1 + N	240 Vac	6	30	26	10	5, 10, 15, 20, 25, 30, 40, 50, 63	R 2 135.00	QF17A...
Commercial / Industrial Earth Leakage Protection Device Single Phase without Overload Protection (Dual Mount) ¹									
QF17C ¹	1 + N	240 Vac	6	30	26	10	63	R 1 474.00	QF17C63
Residential / Commercial Earth Leakage Protection Device Three Phase with Overload Protection (Dual Mount)									
QA36AW	3 + N	415 Vac	3	30	78	5	6, 10, 15, 20, 25, 30, 40, 50, 63	R 3 481.00	QA36AW2...
Residential / Commercial Earth Leakage Protection Device Three Phase without Overload Protection (Dual Mount) ¹									
QA36CW	3 + N	415 Vac	3	30	78	5	63	R 2 251.00	QA36CW63
Commercial / Industrial Earth Leakage Protection Device Single Phase with Overload Protection (Mini Rail & Front Mount)									
SF15A	1 + N	240 Vac	6	30	65	10	80, 100	R 3 006.00	SF15K...
Commercial / Industrial Earth Leakage Protection Device Single Phase without Overload Protection (Mini Rail & Front Mount) ¹									
SF15C ¹	1 + N	240 Vac	6	30	65	10	100	R 2 056.00	SF15A99
Commercial / Industrial Earth Leakage Protection Device Three Phase with Overload Protection (Mini Rail & Front Mount)									
SF36A	3 + N	415 Vac	6	30	117	5	15, 20, 30, 40, 50, 60, 70, 80	R 3 956.00	SF35K...
Commercial / Industrial Earth Leakage Protection Device Three Phase without Overload Protection (Mini Rail & Front Mount) ¹									
SF36C ¹	3 + N	415 Vac	6	30	117	5	80	R 3 323.00	SF35A80

Note:

1. Required to be backed by suitable Short Circuit Protection Device (SCPD).



SM Range Earth Leakages



SM15



SM36

110 Vac Mining/Industrial Earth Leakage Protection Device, Single Phase with Overload Protection (Mini Rail & Front Mount)									L2
Type	Poles	Voltage	kA	mA	Width (mm)	Std. Pack	Rating (A)	Price Ea. excl. VAT	Order No.
SM15A	1 + N	110 Vac	6	30 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SN15K...
SM15A	1 + N	110 Vac	6	50 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SN15L...
SM15A	1 + N	110 Vac	6	100 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SN15M...
SM15A	1 + N	110 Vac	6	250 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SN15N...
SM15A	1 + N	110 Vac	6	375 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SN15P...
SM15A	1 + N	110 Vac	6	500 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SN15Q...
SM15A	1 + N	110 Vac	6	1000 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SN15R...

240 Vac Mining / Industrial Earth Leakage Protection Device, Single Phase with Overload Protection (Mini Rail & Front Mount)									L2
Type	Poles	Voltage	kA	mA	Width (mm)	Std. Pack	Rating (A)	Price Ea. excl. VAT	Order No.
SM15A	1 + N	240 Vac	6	50 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SM15L...
SM15A	1 + N	240 Vac	6	100 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SM15M...
SM15A	1 + N	240 Vac	6	250 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SM15N...
SM15A	1 + N	240 Vac	6	375 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SM15P...
SM15A	1 + N	240 Vac	6	500 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SM15Q...
SM15A	1 + N	240 Vac	6	1000 mA	65	10	10, 15, 20, 30, 40, 50, 60, 80, 100	R 3 006.00	SM15R...

110 Vac Mining / Industrial Earth Leakage Protection Device, Three Phase with Overload Protection (Mini Rail & Front Mount)									L2
Type	Poles	Voltage	kA	mA	Width (mm)	Std. Pack	Rating (A)	Price Ea. excl. VAT	Order No.
SM36A	3 + N	110 Vac	6	30 mA	117	5	10, 15, 20, 30, 40, 50, 60, 80	R 3 956.00	SN35K...
SM36A	3 + N	110 Vac	6	50 mA	117	5	10, 15, 20, 30, 40, 50, 60, 80	R 3 956.00	SN35L...
SM36A	3 + N	110 Vac	6	100 mA	117	5	10, 15, 20, 30, 40, 50, 60, 80	R 3 956.00	SN35M...
SM36A	3 + N	110 Vac	6	250 mA	117	5	10, 15, 20, 30, 40, 50, 60, 80	R 3 956.00	SN35N...
SM36A	3 + N	110 Vac	6	375 mA	117	5	10, 15, 20, 30, 40, 50, 60, 80	R 3 956.00	SN35P...
SM36A	3 + N	110 Vac	6	500 mA	117	5	10, 15, 20, 30, 40, 50, 60, 80	R 3 956.00	SN35Q...
SM36A	3 + N	110 Vac	6	1000 mA	117	5	10, 15, 20, 30, 40, 50, 60, 80	R 3 956.00	SN35R...

415 Vac Mining / Industrial Earth Leakage Protection Device, Three Phase with Overload Protection (Mini Rail & Front Mount)									L2
Type	Poles	Voltage	kA	mA	Width (mm)	Std. Pack	Rating (A)	Price Ea. excl. VAT	Order No.
SM36A	3 + N	415 Vac	6	50 mA	117	5	15, 20, 30, 40, 50, 60, 80	R 3 956.00	SM35L...
SM36A	3 + N	415 Vac	6	100 mA	117	5	15, 20, 30, 40, 50, 60, 80	R 3 956.00	SM35M...
SM36A	3 + N	415 Vac	6	250 mA	117	5	15, 20, 30, 40, 50, 60, 80	R 3 956.00	SM35N...
SM36A	3 + N	415 Vac	6	375 mA	117	5	15, 20, 30, 40, 50, 60, 80	R 3 956.00	SM35P...
SM36A	3 + N	415 Vac	6	500 mA	117	5	15, 20, 30, 40, 50, 60, 80	R 3 956.00	SM35Q...
SM36A	3 + N	415 Vac	6	1000 mA	117	5	15, 20, 30, 40, 50, 60, 80	R 3 956.00	SM35R...

Notes:
* Please contact CBI to determine the earth leakage configuration and availability.
Max cable size 50 mm² - SM.

